

High quality day/night dome color cameras

Art. no. 14202 **Model VC-SLDI-48022P-FIT**
 Art. no. 14212 **Model VC-SLDI-48026P-TN**
 Art. no. 14200 **Model VC-HSDI-48022P-FIT**
 Art. no. 14214 **Model VC-HSDI-48026P-TN**
 Art. no. 14235 **Model VC-HSDI-48018P-TNPZ**

Art. no. 14216 **Model VC-SLDA-48022P-FIT**
 Art. no. 14217 **Model VC-SLDA-48026P-TN**
 Art. no. 14218 **Model VC-HSDA-48022P-FIT**
 Art. no. 14219 **Model VC-HSDA-48026P-TN**
 Art. no. 14245 **Model VC-HSDA-48018P-TNPZ**



Art.no. 14202 / 14212



Art.no. 14200 / 14214 / 14235



Wall mounting

Art.no. 14216 / 14217
 Art.no. 14218 / 14219
 Art.no. 14245



Ceilings mounting
 optional with ceiling
 holder art.no. 14227




Ceiling assembly frame

Art.no. 14203 hole Ø 190mm for art.nr. 14202 / 14212
 Art.no. 14201 hole Ø 165mm for art.nr. 14200 / 14214 / 14235

Art. no.	14202	14212	14200	14214	14235	14216	14217	14218	14219	14245
Montage place (outdoor IP65):	Indoor	Indoor	Indoor	Indoor	Indoor	Outdoor	Outdoor	Outdoor	Outdoor	Outdoor
Camera type:	FIT	T/N	FIT	T/N	T/N	FIT	T/N	FIT	T/N	T/N
Horizontal resolution:				> 480 lines (752 x 582 Pixel)						
Snooper scope:				1/4" Super-HAD-CCD-Chip						
Minimum illumination (Lux):	FIT 0,001	B/W 0,1	FIT 0,001	B/W 0,1	B/W 0,1	FIT 0,001	B/W 0,1	FIT 0,001	B/W 0,1	B/W 0,1
and in color (F1,6)					1 Lux					
Spectral sensitivity:	800nm	1100nm	800nm	1100nm	1100nm	800nm	1100nm	800nm	1100nm	1100nm
Advanced digital white balance:				ATW, AWB or MWB adjustable 2000 -10000°K						
Modulation depth:				80%						
Enhancer: Vertikal und horizontal:				Digitale Aperture lifting						
Gamma-correction:				0,45						
Knee function:				Lifting contour						
Signal-to-noise ratio:				50 dB						
AGC / ALC:				28 dB / 72 dB						
Automatic electrical shutter				1/50 - 1/10000 sec.						
Intelligent backlight compensation:				Available						
Smeareffect / LAG:				0,004 % / Zero						
Scanning system / Video output:				PAL, 625 Zeilen, 50 Hz / FBAS, 1 Vss an 75 Ohm						
Power source:	12VDC	12VDC	24VAC	24VAC	24VAC	24VAC	24VAC	24VAC	24VAC	24VAC
Max. Strom:					1,5A					
Environmental temperature (°C):	+5 - +50	+5 - +50	+5 - +50	+5 - +50	+5 - +50	-20 - +50	-20 - +50	-20 - +50	-20 - +50	-20 - +50
Environmental humidity:				To 95 %						
Electrical safety:				EN 60065+60950						
EMC:				EN 50081+82, CE-Zertififikation						
Optical zoom adjustable (mm):	3,9-85,8	3,5-91	3,9-85,8	3,5-91	4,1-73,8	3,9-85,8	3,5-91	3,9-85,8	3,5-91	4,1-73,8
Digital zoom adjustable:				To 10-fold						
Turning and decline region:	360°/90°	360°/90°	360°/180°	360°/180°	360°/180°	360°/90°	360°/ 90°	360°/180°	360°/180°	360°/180°
Turning / decline cruise (max):	15°/10°	15°/10°	300°/120°	300°/120°	300°/120°	15°/10°	15°/10°	300°/120°	300°/120°	300°/120°
On-Screen Display:				For camera parameter agreement						
Activation about:				RS-485 remote control (multi protocol)						
Direct alarm contact:	-----	-----	yes (4)	yes (4)	yes (4)	-----	-----	yes (4)	yes (4)	yes (4)
Alarm aktivation about RS-485:			optional with heap stack alarm distributor art.no. 14206							
Preprogramming:				128 position (preset)						
Panorama tour:				Yes						
System adress:				255						
Integration to max.:	128-fold	-----	128-fold	-----	-----	128-fold	-----	128-fold	-----	-----
Movable IR-filter:	-----	yes	-----	yes	yes	-----	yes	-----	yes	yes
Privat zone mask:	-----	-----	-----	-----	yes	-----	-----	-----	-----	yes
Suitable remote control:				All VC remote control with RS 485 interface						
Weight:	2kg	2kg	2kg	2kg	2kg	4kg	4kg	4kg	4kg	4kg
Measurements (Ø x Hmm):	185 x 180	185 x 180	140 x 210	140 x 210	140 x 210					
Incl. bracket (Ø x Hmm):						210 x 300	210 x 300	210 x 300	210 x 300	210 x 300
Accessories - power supply:					yes					
- wall mount :	-----	-----	-----	-----	-----	yes	yes	yes	yes	yes

Zubehör




Art.no. 20616
Corner assembly mount
for wall mount
Measurements:
B= 195mm
H= 220mm
T= 120mm



Art.no. 20611
Ceiling mount
for dome housing
Measurements:
L= 300mm
ØDecke= 140mm
ØDome= 70mm



Art.no. 14227
Ceiling mount
for dome housing
Measurements:
L= 110mm
ØDecke= 100mm
ØDome= 70mm



Art.no. 20613
Pole mount for wall mount
(Suitable for pole diameter
60-150 mm)
Measurements:
B= 180mm
H= 225mm
T= 135mm



Art.no. 20621
Extension
for art.no. 20611
Measurements:
L= 300mm
Ø= 30mm



Art.no. 14221
Angle shape
extension
Measurements:
L 1= 105mm
L 2= 105mm