

Vandalism protected dome housing incl. p/t head, RS-485 and preset position (PP)

Art. no. 14223

Model name VC-VSN-DOME-PL

Version RS-485, p/t head and (PP)

Finery installation



VDE CE EMC

Included in delivery:

Vandalism protected housing with RS-485 interface, p/t head for 32x32mm board cameras and preset position (PP), video connection cable with BNC and DC socket and screw connections for RS-485 control

Advisable accessories:

Stabilized power supply

12V DC/400mA

Keypad

Art.no. 20114

Art.no. 14215

Technical data

Assembling place:	Indoor and protected outdoor area
Special functions:	Preset position (PP), 360° angle of rotation
Environmental temperature:	-10 up to +50 °C
Horizontal rotation angle:	360° / 4° per sec.
Vertical tilt angle:	90° / 6° per sec.
Housing construction:	Metal
Housing color:	Dome housing: beige Internal screen: black Dome: plexiglas, clear
Dimensions:	See drawing
Weight:	600g
Fastener for board camera:	Plastics arena
Electrical safety:	60065+60950 class III
Power source:	12V DC
EMC:	EN 50081+82, CE certification
Cutting site:	RS-485, 2 conductor
Connections: (Video)	Connection cable with BNC socket
(Voltage)	DC socket
(Control RS-485)	2pin screw connection

Dimensions



Connections

