

System keypad with RS-485 / RS-422 - BUS

Art. no. 14370

Model name VC-SYS-CONTROL

Version VC protocol

Controls



- ① 4-digit digital display indicating the accessed equipment (Speed-Dome, camera, monitor, conduit box)
- ② Functional keys for multiplexer, DVR's and crossbar
- ③ Lens control (zoom, focus, iris)
- ④ Button for selecting cameras, monitors and alarm
- ⑤ Joystick (3 axial)
- ⑥ Programming menu

VDE CE EMC

Technical Data

Communication

Interface

Protocol

Display

Controls of dome

Console

Alarm masking / 2 transmission

Programming

MTBF

Environmental temperature

Environmental humidity

Electrical safety (VDE)

RS-485 connection

Power source / consumption

Measurements (BxTxH)

Weight

Color

Supplied accessories

RS-485 / 422 with high voltage protection

VC protocol

LCD with background illumination, 4 lines per 20 characters

3 axial joystick, button

Not controlling plastic button VR

LCD about RS-485

Cameras, crossbar, multiplexer and alarm administration

80.000 hours

0° C - 50° C

Bis 95% (without condensation)

IP-40 / KI.II

RJ45 / screw clamp

12V DC / 5 W

355mm x 209mm x 109mm

2,5 kg

Silver / black

Conduit box with power supply 230V AC

3m connection cable with RJ45 plugs



Connection:
RS-485 screw clamp / RJ45
230V AC power supply