

System keypad with RS-485 - BUS

Art. no. 14381

Model name VC-SYS-MULTI-CON

Version multi protocol

Controls



- ① 4-digit digital display indicating the accessed equipment (Speed-Dome, camera, monitor, dvr, alarm control)
- ② Functional keys for camera, multiplexer, DVR and crossbar
- ③ Lens control (zoom, focus, iris)
- ④ Button for selecting cameras, monitors and alarm
- ⑤ Joystick (3 axial)
- ⑥ Programming menu

VDE CE EMC

Technical Data

Communication

Interface

Integrated protocols: Camera
Digital recorder
Multiplexer
Telemetry video matrix
P/T heads

Alarm control

Display

Controls of dome

Console

Alarm masking / 2 transmission

Programming

MTBF

Environmental temperature

Environmental humidity

Electrical safety (VDE)

RS-485 connection

Power source / consumption

Measurements (BxTxH)

Weight

Color

Standard accessory

Compatible VC article: Camera

Digital recorder

Multiplexer

Telemetry video matrix

P/T heads

Alarm control

RS-485

VC, Pelco, Panasonic, Samsung and DSCP

VC and DSCP

VC and DSCP

VC

VC, Pelco, Panasonic, Samsung and DSCP

Programming (alarm receiver)

LCD with background illumination

3 axial joystick, button

Not controlling plastic button VR

LCD about RS-485

Cameras, crossbar, multiplexer, DVR and alarm administration

80.000 hours

0° C - 50° C

To 95% (without condensation)

IP-40 / K1.II

RJ45 / screw clamp

12V DC / 5 W

355mm x 209mm x 109mm

2,5 kg

Silver / black

Connection box with power supply 230V AC

3m connection cable with RJ45 plugs

14208, 14223, 13815, 13825, 14202, 14212, 14200, 14214,

14235, 14216, 14217, 14218, 14219, 14245

13155, 13160, 13165, 13170, 13173, 13186

20147-Z, 20235-Z

14306, 14362, 14310

14380, 14385, 20624-PP, 20602

14350, 14355, 14358



Connection:

RS-485 screw clamp / RJ45

230V AC connection cable