

Quad b/w and color

Art. no. 15015	Model name VC-BWQ-4S	Version 4-fold b/w quad without alarm
Art. no. 15010	Model name VC-BWQ-4AMS	Version 4-fold S/W quad with alarm
Art. no. 15000	Model name VC-CQ-4ZAS	Version 4-fold Farb quad with alarm















Art.no.: 15015

Art.no.: 15010

Art.no.: 15000

VDE CE EMC

Technical data

	Art.no. 15015 VC-BWQ-4S	Art.no. 15010 VC-BWQ-4AMS	Art.no. 15000 VC-CQ-4ZAS
Model name			
Video inputs	4x BAS (BNC)	4x BAS (BNC)	4x FBAS (BNC)
Adjustment of signals	Auto	Adjustable	Adjustable
Loop in inputs	No	No	No
Video outputs	2x BAS (BNC)	2x BAS (BNC)	2x FBAS (BNC)
Switching cycle	Yes (3 sec.)	Yes (adjustable)	Yes (adjustable)
Scanning system	CCIR	CCIR	PAL
Alarm inputs	No	4	4
Motion detected	No	Yes	Yes
Alarm output	No	Yes	Yes
Alarm reset	No	Internal	Internal
Alarm length	No	Adjustable	12 sec.
Alarm protocol	No	Yes	Yes
Data masking	No	Yes	Yes
Zoom function	No	Yes	Yes
Mirror picture function	No	No	Yes
Picture in picture masking	No	Yes (2x)	Yes (3x)
Complete picture per Sec.	20	25	25
Grey scales (b/w handling)	8bit 256 steps	8bit 256 steps	8bit 256 steps
Resolution	720x576 points	720x576 points	720x576 points
Color scale	No	No	24bit (16 Mio. tones)
Signal-to-noise ratio	>62 dB	>62 dB	>62 dB
Synchronisation		Intern/Timebase, all cameras	
Video breakdown detection	No	Yes	Yes
Environmental temperature		5° to + 40° C	
Environmental humidity		To 90% (without condensation)	
Interference emission		EN 50081-1, 55011 class B	
Interference resistance		EN 50082-2, 50204, 61000-4	
Reliability		EN 60950, 60065	
Protection class (VDE)		IP - 40 / cl. 3	
Connection:			
Video		BNC socket	
Voltage		12 V DC	
Power source	3 Watt	5 Watt	12 Watt
Alarm	No	DSUB 9 socket	DSUB 9 socket
RS-485	No	No	No
Accessories included:			
Remote control	No	No	IR remote control
Power supply	12V DC / 1A	12V DC / 1A	12V DC / 1A
Measurements (W x H x Dmm)	220 x 44 x 210	290 x 50 x 230	210 x 38 x 160 mm
Weight	1,4 Kg	1,3 Kg	1,1 Kg