


1/3" color antivandalism dome camera with manual vario lens

Art. no. 15480V-M3/6

Model name VC-VFKUP-380-M3/6

Version 380TVL 2,6-6mm man. vario lens



Standard packing:
color antivandalism dome camera with man. vario lens and 1,2m connection cable equipped with: DC plug and BNC socket for video

Accessories:
Stabilized power supply
12V DC/400mA (art.no. 20114)


VDE (E) EMC

**VC-Products
mean
high quality
and
reliability
with
German
engineering
and
design**

Technical data

Resolution:	380TVL (512 x 582 Pixel)
Minimum illumination:	0,5 Lux / F 1,4
Pick-up device:	1/3" Sony Super HAD CCD-Chip
Signal working:	Digital (DSP)
Spectral area:	380 up to 800nm wave length
DIP switch for:	DC resp. Shutter Mode, Flickerless (ON/OFF), Mirror (ON/OFF), Backlight (ON/OFF)
Gamma correction:	0,45
Knee function:	yes, for edge enhancement
Signal to noise-ratio:	> 45 dB
AGC:	Max. 26 dB
Synchronisation:	Internal
Elektr. Shutter:	1/50 - 1/100000 sec.
Backlight compensation:	Yes (auto)
Smearing effect:	0,004%
LAG:	Zero
Scanning system:	PAL, 625 lines, 50 Hz
Video output:	FBAS 1 Vss / 75 Ohm
Power source / consumption:	12 (8-18)V DC, 0,2 A (reverse batterie protect.)
Environmental temperature:	-10 up to +50°C
Environmental humidity:	To 90%
Weight:	790 g
Measurements:(DxH):	140 x 95 mm
Lens:	2,6-6mm man. vario (43-86° horizontal)
Lens mount holder:	12mm lens holder
Iris:	Fixed
Focussing:	Manual
Specific features:	DIP switch programming
Mounting reattachments:	Ceiling or wall mounting (3achsial)
Mounting place:	Indoor and outdoor area (IP67)
Housing construction:	Shock-resistant metal housing (beige), dome Poly Karbonat
Camera housing typ:	For board cameras 1x 32x32 up to 2x 38x38mm

Spectral sensitivity of camera CCD-Chip



Open dome with board camera and DC vario lens

