

Quality 1/3" day/night color system camera

Art. no. 15760-HR Model name VC-OSD-55230-TN

Version 550TVL / 230V AC, d/n, OSD





**VC-Products
mean
high quality
and
reliability
with
German
engineering
and
design**

Technical data

Horizontal resolution:.....550 tv lines (752 x 582 pixel) (color)
600 tv lines (752 x 582 pixel) (b/w)
Minimum illumination:.....0,1 Lux / F 1,4 (color)
0,01 Lux / F 1,4 (b/w)
Pick-up device:.....1/3" Sony Super HADII CCD-Chip
Signal machining:.....Digital (DSP)
Spectral sensitivity:.....380 up to 800 nm wave length (color)
380 up to 1100 nm wave length (b/w)
OSD menu:.....Shutter, manual and auto. white balance, Back-
light, AGC, Contrast, Gamma correction, Motion
detection, 4x privat zone area, mirror function
Synchronisation:.....Internal
Electrical shutter:.....1/50 - 100000 sec.
Smeareffekt:.....0,004%
LAG:.....Zero
Scanning system:.....PAL, 625 lines, 50 Hz
Video output:.....FBAS, 1 Vpp 75 ohm
Power source / consumption:.....230V AC / 3W
Environmental temperature:.....-10 up to +55 °C
Environmental humidity:.....Up to 90%
Electrical safety VDE:.....EN 60065+60950
EMC:.....EN 50081+82, CE-certification
Maximum vibration:.....8 G
Mounting attachment:.....1/4" screw threads
Weight:.....500 g
Measurements:(WxHxD).....50 x 60 x 128 mm
Lens mount:.....CS-Mount and C-Mount Adapter
Iris:.....Electr. shutter and DC video signal
Connections:.....230V AC connection 1,8m
Video output BNC
4pin lens socket
Functions range:.....OSD menu
Included accessories:.....C/CS-Mount adapter
4pin lens plug
Suitable accessories:.....lenses, brackets and environmental housings


Spectral sensitivity of camera CCD-Chip



Nr.	Connection
1	Control -
2	Control +
3	Drive +
4	Drive -



Tag



Nacht



Privatzonenmaske