

Vandalism color dome camera in plastics housing


Art. no. 16050	Model name VC-FVKUP90R-38043	Version 380TVL, with 4,3mm fixed lens
Art. no. 14073	Model name VC-FVKUP90R-48043	Version 480TVL, with 4,3mm fixed lens
Art. no. 16051	Model name VC-FVKUP90R-380VF	Version 380TVL, with 4-9mm vario lens
Art. no. 14072	Model name VC-FVKUP90R-480VF	Version 480TVL, with 4-9mm vario lens
Art. no. 14098	Model name VC-KUP90R-PLATTE	Version 125mm Ø



Art.no.: 14098



VDE CE EMC



Standard packing:

Dome camera with lens and 1,2m connection cable equipped with:
DC plug and video BNC socket

Accessories:

Stabilized power supply
12V DC/ 2 A art.no. 20114

Technical data

Minimum illumination:	0,5 Lux / F1,4
Pic-up device:	1/3" CCD-Chip Sharp
Automatic white balance:	2800-8200° K
Enhancer:	Horizontal and vertical
Gamma correction:	0,45 or 1 (DIP switch)
Knee function:	For edge enhancement
Signal-to-noise ratio:	> 58 dB
AGC / ALC:	28 dB / 72 dB (DIP switch)
Synchronisation:	Internal
Electr. shutter:	1/50 - 1/100000 sec. (DIP switch)
Intelligent backlight compensation:	Yes (auto) (DIP switch)
Smeareffect:	0,004%
LAG:	Zero
Scanning system:	PAL, 625 lines, 50 Hz
Video output:	FBAS 1 Vpp / 75 Ohm
Power source / consumption:	9-15 V DC, 0,1 A
Environmental temperature:	-20 up to +50 °C
Environmental humidity:	Up to 95%
Electrical safety VDE:	60065+60950
EMC:	EN 50081+82, CE certification
Impact resistant housing:	Plastics
Dome glass:	Impact resistant polycarbonate
Maximum shock:	80 G
Maximum vibration:	8 G
Reattachments:	4 holes
Weight:	250 g
Measurements:	42x42 mm board
Lens holder:	12 mm screw thread
Iris:	Fixed or DC lenses
Focussing:	Manual (0,5 m up to unlimited)
Connections:(Video, Spg.):	1,2m video connection cable with BNC socket and 12 V DC

Spectral sensitivity of camera CCD-Chip

