

High resolution digital 1/3" B/W cameras (Premium Quality)

Art. No. 20057

Model name VC-HB-60012HR

Version 12V DC


Art. No. 20058

Model name VC-HB-60230HR

Version 230V AC



VDE C E EMC



12V DC Buchse

Wahlschalter für
AES, BLC und
Objektivtyp

Artikel: 20057




Wahlschalter für
AES, BLC und
Objektivtyp

Artikel: 20058

Technical data

Horiz. resolution:	600 lines (752 x 582 Pixel)
Pick up aevide:	1/3" Sony Super HAD CCD-Chip
Min. illumination:	0,01 Lux / F 1,4
Spectral range:	380 bis 1100 nm wave length
Modulation depth:	80%
Enhancer: Horiz.	Digital aperture improvement
Corection:	0,45
Knee Funktion available:	YES
Signal noise:	> 58 dB
AGC / ALC:	Max. 28 dB / 72 dB
Synchronisation:	Internal
Auto. electronic Shutter:	1/50 - 1/100000 sec.
Backlight compensation:	Available (BLC)
Smeareffect:	0,004%
LAG current:	Null
Scanning:	CCIR, 625 lines, 50 Hz
Video output signal:	BAS, 1 Vss an 75 Ohm
Operating voltage / capacity:	12V DC / 3 W (20057) 230V AC / 3 W (20058)
Operating temperature:	-10 up to +50 °C
Relative humidity:	Up to 95%
Electrical safety:	EN 60065+60950
MTBF:	80.000 hours
EMC:	EN 50081+82, CE certification
Maximum shock:	80 G
Maximum vibration:	8 G
Mounting screw threads (1/4"):	optional up or down
Lens mount:	CS-mount and C-mount adapter
Blendensteuerung:	AES, DC or AI lens
Connections	20057: 12 V DC female 20058: 2m line cord with power plug Video output BNC DC lens female
Included accessories:	C/CS mount adapter, spanner ES connector
Suitable accessories:	All VC controller with RS-485
For Art. No. 20057 necessary:	Stabilized plugin power supply 20



Weight:
200g (DC) / 400g (AC)
Dimensions:
L¹ 95mm, L² 110mm
W: 55mm, H: 45mm