


Stabilized power supplies

Art. no. 20114-S **Model name** VC-NT-1213S
Art. no. 18288 **Model name** VC-NT-4805T
Art. no. 14395S **Model name** VC-NT-12/1,2A
Art. no. 20338S **Model name** VC-NT-125T
Art. no. 20331 **Model name** VC-NT-40-24/1,7A

Version Plug-in power supply 12V DC/1,25A
Version Plug-in power supply 48V AC/0,5A
Version Table mount power supply 12V DC/1,0A
Version Table mount power supply 12V DC/5A
Version Table mount power supply 24V AC/1.7A


Art.no. 20114S



Suitable for all 12 V DC cameras with DIN mini sub socket with a max. power of 15 Watt.
 Linelock connection is not available.

Connection:..... DIN mini sub plug 

Art.no. 18288



Suitable for all 48 V DC devices with DIN mini sub socket with a max. power of 24 Watt.
 Linelock connection is not available.

Connection:..... 


Art.no. 20331



Suitable for all 24 V AC cameras with a max. power of 40 Watt.
 Cable with soldered glands.

Connection:..... cable with pair of wires, 24 V AC

Art.no. 14395G, 20338S



Suitable for all 12 V DC equipment with DIN mini sub socket with a max. power 12 resp. 60 Watt

Connection:..... DIN mini sub plug 

Technical data

Application area:..... Indoor (socket)
 Housing:..... Plastics, graphite black (RAL9011)
 Power source:(20114-S, 18288).... 100-240V AC, euro plug
 (14395S)..... 110-265V AC, 1,5m power /euro plug
 Power source:(20338S)..... 100-240V AC, 1,5 m power /euro plug
 (20331)..... 230V AC, 1,5m power cord with
 euro plug
 Cable (low voltage site):..... 1,5m (all power supplies)
 Environmental temperature:..... +5° to + 40°C
 Environmental humidity:..... To 90%
 Electrical safety VDE:..... 60065 and 60950 / IP40 / class 1
 Interference resistance:..... Equivalent EN 50082-2, IEC 801
 EMC:..... EN 50081+82, CE certification
 Measurements:(20114-S)..... 29 (W) x 46 (H) x 68 (D) mm
 (18288)..... 31 (W) x 52 (H) x 78 (D) mm
 (14395S)..... 50 (W) x 31 (H) x 100 (D) mm
 (20338S)..... 50 (W) x 30 (H) x 110 (D) mm
 (20331)..... 65 (W) x 53 (H) x 110 (D) mm
 Weight:(20114-S)..... 150g
 (18288)..... 200g
 (14395S)..... 200g
 (20338S)..... 300g
 (20331)..... 600g