

Stabilized power supplies

Art. no. 20114S	Model name VC-NT-1213S	Version Plug-in power supply 12V DC/1,3A
Art. no. 20115	Model name VC-NT-24/2	Version Plug-in power supply 24V AC/0,4A
Art. no. 14395G	Model name VC-NT-12/1A	Version Table mount power supply 12V DC/1,0 A
Art. no. 20373S	Model name VC-NT-1225T	Version Table mount power supply 12V DC/2,5 A
Art. no. 20338S	Model name VC-NT-125T	Version Table mount power supply 12V DC/5 A
Art. no. 20331	Model name VC-NT-40-24/1,7A	Version Table mount power supply 24V AC/1.7 A
Art. no. 20643	Model name VC-Power cord	Version 230V AC Power cord

Art.no. 20114S



VC-NT-1213S

Suitable for all 12 V DC cameras with DIN mini sub socket
Linelock connection is not available

Connection:..... DIN mini sub plug 

Art.no. 20115, 20331




VC-NT-24/2, VC-NT-40-24/1,7A

Suitable for all 24 V AC cameras
Cable with soldered glands.

Connection:..... cable with pair of wires, 24 V AC

Art.no. 14395G, 20373S, 20338S



VC-NT-12/1A, VC-NT-1225T, VC-NT-125T

Suitable for all 12 V DC equipment with DIN mini sub socket with a max. power 12, 30 resp. 60 Watt

Connection:..... DIN mini sub plug 

Art.no. 20643



VC-Power cord

1,8m connection cable for 230V AC with shook-proof plug and Kaltgeräte-stecker, for connection ours power supplies and video components.

Technical data

Application area:.....	Indoor (socket)
Housing:.....	Plastics, graphite black (RAL9011)
Power source:(20114S).....	100-240V AC, euro plug
(20115).....	230V AC, euro plug
(14395G).....	110-265V AC, 1,5m power /euro plug
Power source:(20373S, 20338S).....	100-240V AC, 1,5 m power /euro plug
(20331).....	230V AC, 1,5m power cord with euro plug
Cable (low voltage site):.....	1,5m (all power supplies)
Environmental temperature:.....	+5° to + 40°C
Environmental humidity:.....	To 90%
Electrical safety VDE:.....	60065 and 60950 / IP40 / class 1
Interference resistance:.....	Equivalent EN 50082-2, IEC 801
EMC:.....	EN 50081+82, CE certification
Measurements:(20114S).....	32 (W) x 46 (H) x 75 (D) mm
(20115).....	55 (W) x 50 (H) x 80 (D) mm
(14395G).....	50 (W) x 28 (H) x 100 (D) mm
(20373S).....	55 (W) x 35 (H) x 100 (D) mm
(20338S).....	50 (W) x 30 (H) x 110 (D) mm
(20331).....	65 (W) x 53 (H) x 110 (D) mm
Weight:(20114S).....	150g
(20115).....	400g
(14395G).....	150g
(20373S).....	300g
(20338S).....	300g
(20331).....	600g