

Automatic camera switch with 4,8 or 16 camera inputs

Art. no. 20148	Model name VC-AKU-4/1
Art. no. 20149	Model name VC-AKU-AL-8/2
Art. no. 20150	Model name VC-AKU-AL-16/2



20148



20149



20150

VDE CE EMC

Model name	VC-AKU-4/1 (20148)	VC-AKU-AL-8/2 (20149)	VC-AKU-AL-16/2 (20150)
Video inputs	4x FBAS (BNC)	8x FBAS (BNC)	16x FBAS (BNC)
Monitor outputs	1x FBAS (BNC)	2x FBAS (BNC)	2x FBAS (BNC)
Video pegel in-/output	0,7 - 2 Vss / 75 Ohm	0,7 - 2 Vss / 75 Ohm	0,7 - 2 Vss / 75 Ohm
Scanning system	All standards	All standards	All standards
Signal-to-noise ratio	> 60 dB	> 60 dB	> 60 dB
Bandwidth	10 MHz (3dB)	10 MHz (3dB)	10 MHz (3dB)
Absorbability of crosstalk	>46 dB / 10 MHz	>46 dB / 10 Mhz	>46 dB / 10 Mhz
Sequence	1-30 sec./picture	1-10 sec./picture	1-10 sec./picture
Droop	3% / 10 MHz	3% / 10 MHz	3% / 10 MHz
Frequenz area	2 Hz - 45 MHz / 0,5 dB	2 Hz - 45 MHz / 0,5 dB	2 Hz - 45 MHz / 0,5 dB
Alarm inputs (TTL Pegel)	No	Yes (8 shutter)	Yes (16 shutter)
Alarm outputs	No	Yes (1 changer)	Yes (1 changer)
Alarm reconsignment	-	Auto reset 1-60 sec. resp. manual	Auto reset 1-60 sec. resp. manual
Acoustic alarm message	No	Additional switchable	Additional switchable
MTBF	80.000 hours	80.000 hours	80.000 hours
Environmental temperature	0° to+ 40° C	0° to + 40° C	0° to + 40° C
Environmental humidity	To 90% (without condensation)	To 90% (without condensation)	To 90% (without condensation)
Interference emission	EN 50081-1, 55011 class B	EN 50081-1, 55011 class B	EN 50081-1, 55011 Klasse B
Interference resistance	EN 50082-2, 50204, 61000-4	EN 50082-2, 50204, 61000-4	EN 50082-2, 50204, 61000-4
Reliability	EN 60950, 60065	EN 60950, 60065	EN 60950, 60065
protection class (VDE)	IP - 40 / cl. I	IP - 40 / cl. I	IP - 40 / cl. I
Connection:			
Video	BNC socket	BNC socket	BNC socket
Voltage	230 V AC	230 V AC	230 V AC
Power output	2 watt	5 watt	5 watt
Alarm	-	8 Schraubklemmanschlüsse	16 Schraubklemmanschlüsse
Housing	Sheet steel	Sheet steel	Sheet steel
Housing color	Beige	Beige	Beige
Measurements (W x H x D)	300 x 44 x 220 mm	420 x 44 x 220 mm	420 x 44 x 220 mm
Weight	1,8 Kg	2,8 Kg	2,8 Kg
19" fastening 1HE	Art.no.: 13201	Art.no.: 13200	Art.no.: 13200