

Wireless video systems (export only)

Art. no. 20416	Model name VC-24G-SET-100	Version transmitter / receiver max. 100m
Art. no. 20419	Model name VC-24G-SET-500	Version transmitter / receiver max. 200m
Art. no. 20418	Model name VC-24G-REV	Version receiver for art.no. 20416 / 20419

transmitter and receiver



Technical data for transmitter and receiver

Frequenzy area.....	2,4 up to 2,4835 GHz
Antenna for indoor area	Removeable with SMA plug
Channel mode switch	4way DIP switch
Modulations type	FM modulation for audio and video
Input sockets	RCA socket 2x audio / 1x video
Adapter for video	RCA plug at BNC socket
12V DC socket	Small devices plug female 5mm Ø
Suitable connector power supply:	Included in delivery
For receiver:	9V DC
For transmitter:	6V DC
Video bandwidth 8 MHz b/w	CCIR / BAS / 600 TVL
color	PAL / FBAS / 480 TVL
Environmentaltemperature	+10 bis +40° C
Environmental humidity	Bis 95%
Electrical safety (VDE)	60065+60950
MTBF	80.000 hours
EMC	EN 50081+82, CE certification
Maximum shock	80 G
Maximum vibration	8 G
Weight	250 g
Measurements	W=60mm H=30mm D=110mm
Antenna	L=75mm diameter = 8mm
Provided accessories per device	1xAdapter RCA/BNC
.....	1x mounting plate
.....	1xAntenna
.....	1x power supply

VDE CE EMC

**VC-Products
mean
high quality
and
reliability
with
German
engineering
and
design**

Technical data for the transmitter

Required input signal	Video 1 Vpp / 75 Ohm
.....	Audio 3 Vpp / 10KOhm

Technical data for the receiver

Input sensitivity	85dBm
Signal S/N ratio	>30dB

