

Network Controller

Art. no. 20471 Model name VC-708Ei



VDE CE EMC

Feature:

- 2 RS-485 serial ports each port supports 8 readers
- 2 Wiegand ports which allow connecting to 2 WG readers
- Supports up to 16 doors each unit and allows linking up to 254 units
- Data retains over 60 days when power failure
- Open-all-doors function when emergency
- Built-in watchdog to prevent the system from halting
- Built-in Ethernet interface for LAN or WAN networking
- Built-in power and RS-485 transmission LED indicator for signal state.
- Multi-door anti-pass-back

VC-708Ei	
User Capacity	50,000
Event Log	50,000
Power Requirement	15-24VDC
Power Consumption	< 2.5W
Communication Interface	Reader Channel : RS485*2 Host Channel : RS485 / Ethernet
Baud Rate	RS-485 9600 bps (N, 8, 1) Ethernet 10M
Environment	-20 °C to +75 °C
DI Input	4+8
Relay Output	4+8
Max. RS-485 Reader Supported	16
Max. WG Reader Supported	2
Anti-pass Back	Yes
Door Group	255
Time Zone	63
Editing Mode	PC Software
Dimensions (mm)	180(H)*231(W)*62(D)
Weight (g)	1,840 ± 50
Housing Material	Metal
Others	UPS Function (No battery included)

